

İçme suyu ve yağmurlama tesisleri için genişleme tankı.




Avantajları

- The composition of the membranes has been made for this range in such a way that there will be no variation in smell, colour or taste.
- The inside of the Airfix vessel has a special coating which prevents oxidation.
- Replaceable bladder.
- CE approved according to EU Pressure Equipment Directive 97/23/EC.

Teknik Özellikler

- Maximum operating pressure: 16.0 bar.
- Replaceable butyl-rubber bladder according to DIN4807/5.
- With single threaded steel connection (no flow-through function).
- Min./ max. working temperature: 1 / 70 °C.
- Material quality:
S235JR.
EN/ISO: P245N.

Tip	Hacim [l]	Boyutlar		Bağlantı	Ağırlık [kg]		Sipariş Kodu
		Ø [mm]	Yükseklik [mm]				
Airfix D-E-B 50/6.0 [16bar]	50	450	830	Rp 1 1/2"	58	1	14703
Airfix D-E-B 80/6.0 [16bar]	80	450	1010	Rp 1 1/2"	69	1	14803
Airfix D-E-B 120/6.0 [16bar]	120	450	1265	Rp 1 1/2"	83	1	14815
Airfix D-E-B 180/6.0 [16bar]	180	550	1255	Rp 1 1/2"	124	1	14821
Airfix D-E-B 240/6.0 [16bar]	240	550	1515	Rp 1 1/2"	147	1	14827
Airfix D-E-B 300/6.0 [16bar]	300	550	1855	Rp 1 1/2"	178	1	14833
Airfix D-E-B 600/6.0 [16bar]	600	750	1840	Rp 2"	282	1	14863
Airfix D-E-B 800/6.0 [16bar]	800	750	2230	Rp 2"	333	1	14883

Tip	Hacim [l]	Boyutlar		Bağlantı	Ağırlık [kg]		Sipariş Kodu
		Ø [mm]	Yükseklik [mm]				
Airfix D-E-B 1000/6.0 [16bar]	1000	750	2730	Rp 2"	398	1	14913
Airfix D-E-B 1600/6.0 [16bar]	1600	1000	2680	Rp 2 1/2"	587	1	14919
Airfix D-E-B 2000/6.0 [16bar]	2000	1200	2400	Rp 2 1/2"	657	1	14923
Airfix D-E-B 3000/6.0 [16bar]	3000	1200	3300	Rp 2 1/2"	864	1	14933

**Çevrimiçi daha fazla bilgi bul:**[man.exp.Airfix_D-E-B.pdf](#)[Declaration of conformity](#)[Kiwa UK Regulation 4](#)[Approval letter Kiwa](#)[Airfix D-E-B 16 bar ADSK](#)[Airfix D-E-B 16 bar RFA](#)[Airfix D-E-B 16 bar DWG](#)[Airfix D-E-B 16 bar STEP](#)[tech.exp.layout-heat.v050709.pdf](#)[ds.eng.airfix-deb.v071218.pdf](#)

Normtherm
Enj. Sist. San. Ve Tic. Ltd. Şti.
Gürpınar Mah. Gürpınar Cd.
Abaylar İş Merkezi No:16/10
, Beylikdüzü-İstanbul - tr

T 212 880 01 14

E info@normtherm.com

I www.flamcogroup.com/tr