

The Flamco Flexcon PA pressurisation assistant is used to monitor heating systems and to assist the installer and end-user with pressure maintenance. The Flexcon PA logs and alerts when pressurisation problems occur and assists in (or control) topping-up the heating system to the correct working pressure. It can also advise on expansion vessel life expectancy without disconnecting the vessel and you can configure monitoring on maintenance intervals for third party components. The Flexcon PA comes with a smartphone/tablet application for advanced and complete delivery of system status and guided maintenance advice.

The Flexcon PA C has the right software to connect to our Remote Service. If you do not intend to take out a remote service subscription with the device, we recommend the standard article.



### Teknik Özellikler

- Suitable for heating systems up to 40,000 l and for addition of glycol-based anti-freeze up to 50%.
- Can be combined with Flamconnect Remote. (Please check your local sales office for availability.)
- Power supply: 5V AC/DC adapter.
- Working system temperature: 0 °C / 90 °C.
- Working ambient temperature: 0 °C / 40 °C.
- Working system pressure up to 3.5 bar.
- Flow rate (filling): 0.7 m<sup>3</sup> / hour.
- Design pressure: PN 6.

### Sınıflandırma Genel Bilgi

<b>Etim Grup</b>	Pressure increase/decrease
<b>Etim Sınıf</b>	Merkezi sistem dolum seti
<b>Marka</b>	FLAMCO

**Sınıflandırma Özellikleri**

Genleşme tankına uygundur	Evet
Kompresörlü genleşme otomatına uygundur	Evet
Nominal iç çap	DN 8
Geri dönüş 1 boru dış çapı	21.3 Millimetre
Filtreli	Hayır
Purjörülü	Hayır
Basınç	0 - 3.5 bar Bar
Genleşme suyu toplama fonksiyonlu	Hayır
With drain funnel	Hayır
Otomatik doldurma fonksiyonlu	Hayır
Doldurma kapasitesi	700 Litre per hour
Yükseklik	71.3 Millimetre
Genişlik	54.5 Millimetre
Derinlik	75.5 Millimetre
Manometreli	Hayır
İzolasyonlu	Hayır

**Çevrimiçi daha fazla bilgi bul:**[Flexcon PA Installation and operating instruction](#)[Manual for installing new firmware](#)[Frequently asked questions](#)[Declaration of conformity](#)[Brochure Flexcon PA](#)[Leaflet Flexcon PA - Consumer](#)[Leaflet Flexcon PA - Installer](#)[Frequently asked questions](#)[Simplified topping-up procedure](#)[Full animation](#)[Full animation](#)[Prescor IC Fill PA](#)

Normtherm  
Enj. Sist. San. Ve Tic. Ltd. Şti.  
Gürpınar Mah. Gürpınar Cd.  
Abaylar İş Merkezi No:16/10  
, Beylikdüzü-İstanbul - tr

T 212 880 01 14  
E [info@normtherm.com](mailto:info@normtherm.com)  
I [www.flamcogroup.com/tr](http://www.flamcogroup.com/tr)