

Compact and totally enclosed digital pressurisation units with electronic pressure transducer and user-friendly microprocessor for use on sealed system in order to provide a minimum system pressure requirement.

The Digifiller is a wall mounted, flow rate (up to 12 l/min) top-up pressurisation unit with 4 litre internal break tank. Self venting pumps and preset options to remove the need for conventional commissioning of the Pressurisation Unit. Ideal for Industrial, commercial or large domestic applications. Available preset to 0.5 bar, 1.0 bar, 1.5 bar or 2.0 bar topup (Delivery) pressure.

Application:

- Commercial, Industrial and Residential.

System Volume (Guide): < 50,000 litres.



Teknik Özellikler

Operating Conditions:

- System temperature range at point of connection: 5 °C / 85 °C.
- Ambient temperature range: 5 °C / 40 °C.
- Pressure rating: PN 10.
- Relative humidity 95% non-condensing.
- Noise Rating Data: < 75 dBA.

Certifications and Standards Applied:

- PED 2014/68/EU Sound Engineering Practice.
- IEE - Electrical Safety Guidance.
- EMC 2004/108/EC.
- BS 7074 Parts 1 to 3.
- Machinery Directive 2006/42/EC.
- Electronic Components have been tested and comply with the EMC Directives.
- EN 61000-6-1: Generic Standards – Immunity standard for industrial environments.
- EN 61000-6-2: Generic Standards – Immunity standard for industrial environments.
- EN 61000-6-3: Generic Standards – Emission standard for residential, commercial and light industrial environment.
- CE marked components, where applicable.
- WRAS approved float valve to BS1212.
- IP54 (BS EN60529) rated controller.

Material of Construction:

- Cabinet: Mild steel CR4 Powder Coated.
- Float: WRAS approved.
- Break Tank: Polypropylene.
- Connection: Brass / Polypropylene.
- Pipework: Braided Flexhose / EPDM / Copper.
- Finish: Powder coated.
- Valves: Brass / PTFE.

Sınıflandırma Genel Bilgi

Marka

FLAMCO

Sınıflandırma Özellikleri

Genleşme tankına uygundur	Evet
Kompresörlü genleşme otomatına uygundur	Evet
Bağlantılar	BSPP iç dişli bağlantı
Nominal iç çap	1/2" (15)
Dolum 1 boru dış çapı	21.3 Millimetre
Geri dönüş 1 boru dış çapı	21.3 Millimetre
Dolum 2 boru dış çapı	21.3 Millimetre
Geri dönüş 2 boru dış çapı	21.3 Millimetre
Maks. Sistem su hacmi	50000 Litre
Filtreli	Hayır
Purjör	Hayır
Basınç	1 - 2.5 bar Bar
Genleşme suyu toplama fonksiyonlu	Hayır
Dolum boru bağlantısı	İç dişli
Maks. Çalışma basıncı	2.5 Bar
With drain funnel	Hayır
Otomatik doldurma fonksiyonlu	Hayır
Dolum bağlantı ölçüsü	21.3 Millimetre
Yükseklik	480 Millimetre
Barrier	Diğer
Genişlik	240 Millimetre
Category of system separator	Diğer
Derinlik	230 Millimetre
With pressure reducer	Hayır
Suitable for softening	Hayır
With system separator	Hayır
Max. temperature at the inlet	85 Degrees celsius
Max. temperature at the outlet	85 Degrees celsius
Suitable for full demineralization	Hayır
Suitable for pH value stabilization	Hayır
Manometreli	Hayır
Suitable for fixed installation	Evet
Suitable for mobile use	Evet
İzolasyonlu	Hayır

Çevrimiçi daha fazla bilgi bul:[Installation and operating instructions](#)[UK Declaration of Conformity](#)[Digifiller DXF](#)[Digifiller RFA](#)[Digifiller STEP](#)[Digifiller IGES](#)[Collection Pressurisation Units REVIT](#)[Collection Pressurisation Units DXF](#)[Collection Pressurisation Units STEP](#)[Collection Pressurisation Units IGES](#)[Overview of spares kits](#)[Spare parts list](#)[Product Datasheet Digifiller](#)

Normtherm
Enj. Sist. San. Ve Tic. Ltd. Şti.
Gürpınar Mah. Gürpınar Cd.
Abaylar İş Merkezi No:16/10
, Beylikdüzü-İstanbul - tr

T 212 880 01 14
E info@normtherm.com
I www.flamcogroup.com/tr