

Avantajları

- Ön basıncın daha uzun korunması için azot gazı dolumu.

Teknik Özellikler

- Değiştirilebilir membranlı butil kauçuğu (DIN 4807/5).

Tip	Hacim [l]	Boyutlar		Bağlantı (F)	Ağırlık [kg]		Sipariş Kodu
		Ø [mm]	Yükseklik [mm]				
Airfix D-E-B 50/6.0 [25bar]	50	450	830	Rp 1 1/2"	59	1	14705
Airfix D-E-B 180/6.0 [25bar]	180	550	1255	Rp 1 1/2"	123	1	14817
Airfix D-E-B 240/6.0 [25bar]	240	550	1515	Rp 1 1/2"	149	1	14829
Airfix D-E-B 600/6.0 [25bar]	600	750	1840	Rp 2"	349	1	14865
Airfix D-E-B 800/6.0 [25bar]	800	750	2230	Rp 2"	417	1	14885
Airfix D-E-B 1000/6.0 [25bar]	1000	750	2730	Rp 2"	500	1	14905

**Çevrimiçi daha fazla bilgi bul:**[man.exp.Airfix_D-E-B.pdf](#)[Declaration of conformity](#)[tech.exp.layout-heat.v050709.pdf](#)[ds.eng.airfix-deb.v071218.pdf](#)

Normtherm
Enj. Sist. San. Ve Tic. Ltd. Şti.
Gürpınar Mah. Gürpınar Cd.
Abaylar İş Merkezi No:16/10
, Beylikdüzü-İstanbul - tr

T 212 880 01 14
E info@normtherm.com
I www.flamcogroup.com/tr