

The Flamco Flexcon PA AutoFill pressurisation assistant is used to monitor heating systems and to assist the installer and end-user with pressure maintenance. The Flexcon PA AutoFill logs and alerts when pressurisation problems occur and assists in (or control) topping-up the heating system to the correct working pressure. It can also advise on expansion vessel life expectancy without disconnecting the vessel and you can configure monitoring on maintenance intervals for third party components. The Flexcon PA AutoFill comes with a smartphone/tablet application for advanced and complete delivery of system status, guided maintenance advice and an automatic filling device for complete automation of topping-up and leak detection of heating systems.



Teknik Özellikler

- Suitable for heating systems with expansion vessels with a system volume up to 40,000 l and for addition of glycol-based anti-freeze up to 50%.
- Can be combined with Flamconnect Remote.
- Power supply: 12V AC/DC adapter.
- Working system temperature: 0 °C / 90 °C.
- Working ambient temperature: 0 °C / 40 °C.
- Working system pressure up to 3.5 bar.
- Flow rate (filling): 0.7 m³ / hour.
- Design pressure: PN 6.

The Flexcon PA AutoFill set includes: Flexcon PA (G ¼" M), AutoFill unit (G ½" M), t-piece (G ½" F), straight coupling (G ½" F), shut-off valve (¼" x ½"), 2x compression nut/ring (15 mm).<><

Sınıflandırma Genel Bilgi

Etim Grup	Pressure increase/decrease
Etim Sınıf	Merkezi sistem dolum seti
Marka	FLAMCO

Sınıflandırma Özellikleri

Genleşme tankına uygundur	Evet
Kompresörlü genleşme otomatına uygundur	Evet
Bağlantılar	BSPP iç dişli bağlantı
Nominal iç çap	1/2" (15)
Dolum 1 boru dış çapı	21.3 Millimetre
Geri dönüş 1 boru dış çapı	21.3 Millimetre
Dolum 2 boru dış çapı	21.3 Millimetre
Geri dönüş 2 boru dış çapı	21.3 Millimetre
Maks. Sistem su hacmi	50000 Litre
Filtreli	Hayır
Purjör	Hayır
Basınç	0 - 3.5 bar Bar
Genleşme suyu toplama fonksiyonlu	Hayır
Dolum boru bağlantısı	İç dişli
Maks. Çalışma basıncı	3.5 Bar
With drain funnel	Hayır
Otomatik doldurma fonksiyonlu	Hayır
Dolum bağlantı ölçüsü	21.3 Millimetre
Yükseklik	136 Millimetre
Barrier	Diğer
Genişlik	57 Millimetre
Category of system separator	Diğer
Derinlik	239 Millimetre
With pressure reducer	Hayır
Suitable for softening	Hayır
With system separator	Hayır
Max. temperature at the inlet	90 Degrees celsius
Max. temperature at the outlet	90 Degrees celsius
Suitable for full demineralization	Hayır
Suitable for pH value stabilization	Hayır
Manometreli	Evet
Suitable for fixed installation	Evet
Suitable for mobile use	Evet
İzolasyonlu	Hayır

Çevrimiçi daha fazla bilgi bul:[Flexcon PA AutoFill Montaj ve kullanma kılavuzu](#)[Manual for installing new firmware](#)[Frequently asked questions](#)[Declaration of conformity](#)[Brochure Flexcon PA](#)[Leaflet Flexcon PA - Consumer](#)[Leaflet Flexcon PA - Installer](#)[Frequently asked questions](#)[Brochure Flamconnect Remote](#)[Simplified topping-up procedure](#)[Full animation](#)[Prescor IC Fill PA](#)

Normtherm
Enj. Sist. San. Ve Tic. Ltd. Şti.
Gürpınar Mah. Gürpınar Cd.
Abaylar İş Merkezi No:16/10
, Beylikdüzü-İstanbul - tr

T 212 880 01 14
E info@normtherm.com
I www.flamcogroup.com/tr