

The Flamco Flexcon PA AutoFill pressurisation assistant is used to monitor heating systems and to assist the installer and end-user with pressure maintenance. The Flexcon PA AutoFill logs and alerts when pressurisation problems occur and assists in (or control) topping-up the heating system to the correct working pressure. It can also advise on expansion vessel life expectancy without disconnecting the vessel and you can configure monitoring on maintenance intervals for third party components. The Flexcon PA AutoFill comes with a smartphone/tablet application for advanced and complete delivery of system status, guided maintenance advice and an automatic filling device for complete automation of topping-up and leak detection of heating systems.



Teknik Özellikler

- Suitable for heating systems with expansion vessels with a system volume up to 40,000 l and for addition of glycol-based anti-freeze up to 50%.
- Can be combined with Flamconnect Remote.
- Power supply: 12V AC/DC adapter.
- Working system temperature: 0 °C / 90 °C.
- Working ambient temperature: 0 °C / 40 °C.
- Working system pressure up to 3.5 bar.
- Flow rate (filling): 0.7 m³ / hour.
- Design pressure: PN 6.

The Flexcon PA AutoFill set includes: Flexcon PA (G ¼" M), AutoFill unit (G ½" M), t-piece (G ½" F), straight coupling (G ½" F), shut-off valve (¼" x ½"), 2x compression nut/ring (15 mm).<><>

Sınıflandırma Genel Bilgi

| | |
|-------------------|----------------------------|
| Etim Grup | Pressure increase/decrease |
| Etim Sınıf | Merkezi sistem dolum seti |
| Marka | FLAMCO |

Sınıflandırma Özellikleri

| | |
|---|------------------------|
| Genleşme tankına uygundur | Evet |
| Kompresörlü genleşme otomatına uygundur | Evet |
| Bağlantılar | BSPP iç dişli bağlantı |
| Nominal iç çap | 1/2" (15) |
| Dolum 1 boru dış çapı | 21.3 Millimetre |
| Geri dönüş 1 boru dış çapı | 21.3 Millimetre |
| Dolum 2 boru dış çapı | 21.3 Millimetre |
| Geri dönüş 2 boru dış çapı | 21.3 Millimetre |
| Maks. Sistem su hacmi | 50000 Litre |
| Filtreli | Hayır |
| Purjör | Hayır |
| Basınç | 0 - 3.5 bar Bar |
| Genleşme suyu toplama fonksiyonlu | Hayır |
| Dolum boru bağlantısı | İç dişli |
| Maks. Çalışma basıncı | 3.5 Bar |
| With drain funnel | Hayır |
| Otomatik doldurma fonksiyonlu | Hayır |
| Dolum bağlantı ölçüsü | 21.3 Millimetre |
| Yükseklik | 136 Millimetre |
| Barrier | Diğer |
| Genişlik | 57 Millimetre |
| Category of system separator | Diğer |
| Derinlik | 239 Millimetre |
| With pressure reducer | Hayır |
| Suitable for softening | Hayır |
| With system separator | Hayır |
| Max. temperature at the inlet | 90 Degrees celsius |
| Max. temperature at the outlet | 90 Degrees celsius |
| Suitable for full demineralization | Hayır |
| Suitable for pH value stabilization | Hayır |
| Manometreli | Evet |
| Suitable for fixed installation | Evet |
| Suitable for mobile use | Evet |
| İzolasyonlu | Hayır |

Çevrimiçi daha fazla bilgi bul:[Flexcon PA AutoFill Montaj ve kullanma kılavuzu](#)[Manual for installing new firmware](#)[Frequently asked questions](#)[Declaration of conformity](#)[Brochure Flexcon PA](#)[Leaflet Flexcon PA - Consumer](#)[Leaflet Flexcon PA - Installer](#)[Frequently asked questions](#)[Brochure Flamconnect Remote](#)[Simplified topping-up procedure](#)[Full animation](#)[Prescor IC Fill PA](#)

Normtherm
Enj. Sist. San. Ve Tic. Ltd. Şti.
Gürpınar Mah. Gürpınar Cd.
Abaylar İş Merkezi No:16/10
, Beylikdüzü-İstanbul - tr

T 212 880 01 14
E info@normtherm.com
I www.flamcogroup.com/tr